




An example of the *Diversion Booming Tactic*. Actual deployment should be adjusted for local conditions.



An example of the *Free-oil Recovery Tactic*. Actual deployment should be adjusted for local conditions.



An example of the *Passive Recovery Tactic*. Actual deployment should be adjusted for local conditions.




Aerial photography of this area is unavailable at this time, but may be included as it becomes available.

Geographic Response Strategies for Western Alaska Subarea, Southern Zone

Kanektok River, WAK-S10

Center of map at 59° 44.90' N Lat., 161° 58.15' W Lon.



This is not intended for navigational use.

ID	Location and Description	Response Strategy	Implementation	Response Resources	Staging Area	Site Access	Resources Protected (months)	Special Considerations
S-10-01 DV	Kanektok River Lat. 59° 44.95'N Lon. 161°55.43'W	Divert and Collect Divert oil to shore side collection location on the shore of the Kanektok River.	Deploy anchors and boom with skiffs (class 6). Place 4 x 300 foot section of fast-water boom in a cascaded pattern at the proper angle to divert incoming oil to the collection sites. Complete the array with 60 ft. of tidal seal boom on the shore that will be used as a collection site. Set up shore-side recovery and tend throughout the tide.	Deployment Equipment 1200 ft. fast-water boom 60 ft. tidal seal boom 12 ea. anchor systems 4 ea. anchor stakes 1 ea. shore-side recovery systems Vessels 2 ea. class 6 Personnel/Shift 4 ea. vessel crew/general techs 2 ea. response techs Tending Vessels 1 ea. class 6 Personnel/Shift 2 ea. vessel crew/general techs 1 ea. skilled tech	Kwinhagak	Via marine waters Chart 16300	Fish- intertidal spawning-salmon(June-Sept.)herring,sheefish, arctic char, white fish Birds-waterfowl, seabird and shorebird concentration Habitat- exposed tidal flats, peat shoreline, marsh, Human use-subsistence	Vessel master should have local knowledge. Title 41 permitting required from ADNRR. Use appropriate measures as outlined in the STAR manual to protect the shoreline. Surveyed: not yet Tested: not yet
S-10-02 PR	Kanektok River Lat. 59° 44.88'N Lon. 161°55.49'W	Passive Recovery Survey the area prior to deployment. Place passive recovery across entrances to the identified slough next to the Kanektok River.	Place and anchor snare line or sorbent boom across the channels of streams/sloughs in Kanektok River. Replace as necessary to maximize the recovery.	Deployment Equipment 100 ft. snare line or sorbent boom 1 ea. small anchor systems 4 ea. anchor stakes (Adjust equipment to reflect survey findings) Vessels/Personnel/Shift Same as S-10-01 Tending Vessels/Personnel/Shift Same as S-10-01	Kwinhagak	Via marine waters Chart 16300	Same as S-10-01	Vessel master should have local knowledge.
S-10-03 FO-S	Kanektok River Nearshore waters in the general area of: Lat. 59° 44.90'N Lon. 161°58.15'W	Free-oil Recovery Maximize free-oil recovery in the offshore & nearshore environment of Kanektok River depending on spill location and trajectory.	Deploy free-oil recovery strike teams upwind and up current of the Kanektok River. Use aerial surveillance to locate incoming slicks.	Deploy multiple free-oil recovery strike teams as required to maximize interception of oil before it impacts sensitive areas.	Kwinhagak	Via marine waters Chart 16300	Same as S-10-01	Vessel master should have local knowledge. Use extreme caution, shallow waters with shifting channels and bars.